

WARNINGS AND SAFETY PRECAUTIONS

The following statements are warnings and safety precautions for the installation, operation, and maintenance of the Aladdin Light Lift. Closely follow the installation instructions when installing the Aladdin Light Lift. Please contact technical support (877) 287-4601 with any questions or concerns regarding the following:

1. The Aladdin Light Lift is designed for use in accessible locations only. See remote installation guide for additional options.
2. Do not exceed wattage capacity of lighting circuitry. Refer to the owner's manual for exact capacity of the light lift.
3. The power source for the motor on the Aladdin Light Lift should be fed by a source other than the light switch leg.
4. The Aladdin Light Lift must be mounted on a level plane in a standard installation. The winch cable should be plumb through the center of the top contact plate on the ceiling box.
5. Never operate the Aladdin Light Lift without weight or tension on the winch cable. This can cause the cable to jump off the winch spool and get caught in the winch gears. Contact technical support toll free at (877) 287-4601 should this situation occur.
6. Never extend the full length of winch cable from the Aladdin Light Lift. This could cause the cable to become reversed on the winch. See Keyswitch operation tag and operation instructions. Refer to the owner's manual for winch cable length on the Aladdin Light Lift. Contact technical toll free at (877) 287-4601 should this occur.
7. Use the permanent screw collar loop furnished with the chandelier.
8. Always make sure the dowel pin is flush in the nipple of the bottom contact plate. The fixture coupler should be threaded over the dowel pin and hole at all times.
9. Always disconnect power source from the Aladdin Light Lift when servicing or performing maintenance.
10. Never use a dimmer switch unless motor is wired on a separate circuit from lights.
11. Always remove packing tape from the winch before operating the light lift.
12. Always wait five seconds between running the Aladdin Light Lift in opposite directions.
13. Only adjust length of chain to adjust chandelier elevation. Never cut or adjust the length of winch cable.

14. Never adjust the cone height on the bottom contact plate. This will interfere with the automatic shutoff system.
15. Never allow the chandelier's canopy to make contact with the ceiling before the contact plates meet. This will cause a canopy sized hole in the ceiling.
16. Always use the supplied thread lock where the fittings attach the chandelier to the bottom contact plate.
17. Never install the Aladdin Light Lift where the ceiling height exceeds the existing length of winch cable. This could cause a reversed cable. The length of cable is marked on the Aladdin Light Lift cover, in the owner's guide, and on the outer shipping box. See warning and safety precaution number 6. Contact technical support toll free at (877) 287-4601 should a reversed cable situation occur.
18. Do not stand or sit underneath the chandelier while operating the Aladdin Light Lift.
19. In remote installations, make sure the winch cable is unobstructed between pulleys.
20. In remote installations, make sure the winch cable travels straight to and from the pulley grooves for proper operation. Keeping the pulleys on the same plane is the best way to insure cable alignment.
21. Do not hang or swing from the Aladdin Light Lift winch cable.
22. Never hang anything but a single stem or chain hung chandelier from the Aladdin Light Lift.
23. Do not hang more than one chandelier from the Aladdin Light Lift.
24. Never use multiple Aladdin Light Lifts to hang one chandelier.
25. Periodically inspect winch cable for frays or kinks. If a fray or kink is detected, contact technical support toll free at (877) 287-4601.
26. Only use fittings, such as the dowel pin, nipples, and fixture couplers, supplied by Aladdin Light Lift to hang the chandelier.
27. Never alter the Aladdin Light Lift from its original state.
28. Always turn the chandelier's lights off at the wall switch when operating the Aladdin Light Lift.